

TECHNICAL DATASHEET

NxN PM Fused Fiber Coupler

Product family	Couplers & Polarization
Key selection	PM / NxN

Technical Specifications

Parameter	-	Unit	Specification
Operating Wavelength	-	nm	780
Excess Loss	Typ.	dB	≤0.8
-	Max.	dB	≤1.0
Extinction Ratio	-	dB	16
Insertion Loss	-	dB	<7.6
Uniformity	-	dB	1.2
Operating Temperature	-	dB	-40to+85
Storage Temperature	-	dB	-40to+85
Configuration	-	dB	4*2
Fiber Length	-	m	1m,otheronrequest
Fiber Type	-	-	PMFiber
Package Dimensions (dia. x L)	-	mm	100*80*10

Configuration Notes

Available wavelength, optical power, fiber, connector, pigtail and package options depend on the selected product configuration. Please include the target application and quantity with your RFQ. Final ordering details are confirmed in the quotation.

www.kernsoptic.com | jenny@kernsoptic.com

Package Dimensions

NxN PM Fused Fiber Coupler

Package reference: 100 x 80 x 10

Catalog-listed package information

Catalog package dimension: 100 x 80 x 10 mm.

Dimensions are shown in millimetres unless otherwise indicated. Final package, pigtail and connector configuration should be confirmed in the quotation.