

TECHNICAL DATASHEET

Mini PM Tap + Optical Isolator Hybrid

Product family	Mini & Hybrid
Key selection	PM

Technical Specifications

Parameter	-	Unit	Specification	-	-	-
Center Wavelength	-	nm	1550,1310	-	1064	-
Operating Wavelength Range	-	nm	±15	-	-	-
Stage	-	-	Single	Dual	Single	Dual
Maximum Excess Loss	-	dB	1.0	1.2	2.2	3.5
Coupling Ratio	-	%	1±0.2%,5±1%,50±2%	-	-	-
Peak Isolation	-	dB	40	52	40	52
Minimum Isolation @ 23°C	-	dB	28	45	28	45
Minimum Return Loss	-	dB	50	-	-	-
Maximum Power (CW)	-	mW	300	-	-	-
Maximum Tensile Load	-	N	5	-	-	-
Fiber Type	-	-	PM Panda Fiber	-	-	-
Package Dimensions	Both axes operating	mm	Φ2.5x20	-	-	-
-	Fast axis blocked	mm	Φ2.5x20	-	-	-
Operating Temperature	-	°C	0 to +70	-	-	-
Storage Temperature	-	°C	-40 to +85	-	-	-

Configuration Notes


Available wavelength, optical power, fiber, connector, pigtail and package options depend on the selected product configuration. Please include the target application and quantity with your RFQ. Final ordering details are confirmed in the quotation.

www.kernsoptic.com | jenny@kernsoptic.com

Package Dimensions

Mini PM Tap + Optical Isolator Hybrid

Package reference: Dia. 2.5x20



Dimensions are shown in millimetres unless otherwise indicated. Final package, pigtail and connector configuration should be confirmed in the quotation.